



CERTIFICATE OF REGISTRATION

This is to certify that

Caledonian Plywood Company Ltd

1 Cardowan Park
Tannochside Park
Uddingston
G71 5PF

Meets the requirements of the BM TRADA **Q-Mark Fire Door Manufacture** scheme to **STD006**

A handwritten signature in black ink, appearing to read 'SR', with a long horizontal stroke extending to the right.

Steve Roberts
Product Certification Operations Manager
For and on behalf of BM TRADA

Certificate Number

034

Date of Initial Certification

10/07/2002

Date of Last Issue

08/08/2023

Date of Expiry

08/07/2026

BM TRADA is a trading name of Warringtonfire Testing and Certification Limited, Chiltern House, Stocking Lane, High Wycombe, Buckinghamshire, HP14 4ND, UK
Registered Office: Warringtonfire Testing and Certification Limited, 3rd Floor, Davidson Building, 5 Southampton Street, London, WC2E 7HA, UK
Reg No. 11371436.

This certificate remains the property of Warringtonfire Testing and Certification Limited. This certificate and all copies or reproductions of the certificate shall be returned to Warringtonfire Testing and Certification Limited or destroyed if requested. Further clarification regarding the scope of this certificate and verification of the certificate is available through BM TRADA or at the above address or at www.bmtrada.com

Registration Schedule

Head Office Address

Factory 1

Factory 2

1 Cardowan Park, Tannochside Park, Uddingston, G71 5PF

1 Cardowan Park, Tannochside Park, Uddingston, G71 5PF

Unit 16, Inter City Way, Bramley, Leeds, LS13 4LY

Scope

Primary Field of Application (FoA) Reports (owned by this certified company)

Either used in isolation, or can be used in conjunction with an appropriate associated document for this company, providing that the FoA report allows it and that both documents are compatible with each other. Where more than one primary FoA is listed for the same doorset type, they cannot be mix and matched, only one FoA is to be chosen and followed precisely.

| Type | FoA Report | Rev | System Supplier owner of Assessment Report | Doorset Description | Integrity Period | Test Type |
|-------|------------|-----|--|---------------------|------------------|-----------|
| Fire | N/A | - | - | - | - | - |
| Smoke | N/A | - | - | - | - | - |

Primary Field of Application (FoA) Reports (owned by and cascaded by a System Supplier)

The revision status of each FoA can be verified on the BM TRADA website under each System Supplier's certification entry. They are either used in isolation, or can be used in conjunction with an appropriate associated document for this company, providing that the FoA report allows it and that both documents are compatible with each other. Where more than one primary FoA is listed for the same doorset type, they cannot be mix and matched, only one FoA is to be chosen and followed precisely.

| Type | FoA Report | System Supplier owner of Assessment Report | Doorset Description | Integrity Period | FoA Standard |
|-------|-----------------|--|---|------------------|--------------|
| Fire | FEA/F98164 | Pacific Rim Wood Ltd | Flamebreak Doorsets for 30 minutes Fire Resistance (Glazed or unglazed) | 30min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | FEA/F02141 | Pacific Rim Wood Ltd | Flamebreak 660 and FF660 Doorsets for 60 minutes Fire Resistance (Glazed or unglazed) | 60min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | Chilt/A01204 | Halspan Limited | Optima 30 Part 1 Timber (glazed and unglazed) | 30min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | FEA/F01205 | Halspan Limited | Optima 60 (Glazed or unglazed) | 60min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | FEA/F97174 | Halspan Limited | Prima 30 Part 1 Timber (glazed and unglazed) | 30min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | FEA/F96103 | Halspan Limited | Prima 60 (Glazed or unglazed) | 60min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | FEA/F97097 | Halspan Limited | Prima 30 Panelled (Glazed or unglazed) | 30min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | Chilt/A01015 | Halspan Limited | Prima 60 Panelled (Glazed or unglazed) | 60min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | Chilt/A05151 | Halspan Limited | Halspan 90 (Glazed or unglazed) | 90min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | WF 389581 | Halspan Limited | Halspan 90 Prima Plus (glazed and unglazed) | 90min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | BMT/CNA/F15082 | Halspan Limited | Halspan 120 (glazed and unglazed) | 120min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | WF 389580 | Halspan Limited | Halspan 120 Prima Plus (Unglazed) | 120min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | Chilt/A13058 | Moralt AG | LAMINESSE FireSmoke 44mm Only (Glazed and Unglazed) | 30min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | Chilt/A13059 | Moralt AG | LAMINESSE FireSmoke 54mm Only (Glazed and Unglazed) | 60min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | WF409922 | Moralt AG | LAMINESSE FireSound 54mm (Glazed or unglazed) | 30min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | WF409922 | Moralt AG | LAMINESSE FireSound 54mm (Glazed or unglazed) | 60min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | WF409923 | Moralt AG | LAMINESSE FireSound 59mm (Glazed or unglazed) | 30min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | WF409923 | Moralt AG | LAMINESSE FireSound 59mm (Glazed or unglazed) | 60min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | BMT/CNA/F14274 | Moralt AG | LAMINESSE FireSound 44mm (Glazed and Unglazed) | 30min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | WF 380559 | Falcon Panel Products Ltd | Strebord® 35+ doorsets for 30 Minutes Fire Resistance (Glazed or Unglazed) | 30min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | WF 380559 | Falcon Panel Products Ltd | Strebord® 38+ doorsets for 30 Minutes Fire Resistance (Glazed or Unglazed) | 30min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | Chilt/A02066 | Falcon Panel Products Ltd | Strebord® 44 door assemblies for 30 Minutes Fire Resistance (Glazed or Unglazed) | 30min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | Chilt/A02067 | Falcon Panel Products Ltd | Strebord® 54 doorsets for 60 Minutes Fire Resistance (Glazed or Unglazed) | 60min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | Chilt/A09104 | Falcon Panel Products Ltd | Strebord® 44 Panelled doorsets for 30 Minutes Fire Resistance (Glazed or Unglazed) | 30min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | Chilt/A10152 | Falcon Panel Products Ltd | Strebord® 54 Panelled Range of Doorsets using Strebord® 54 Panelled Door Blanks in Timber Based Door Frames 60 Minutes Fire Resistance (Glazed or Unglazed) | 60min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | BMT/CNA/F15159 | Falcon Panel Products Ltd | Stredor® 44 doorsets for 30 Minutes Fire Resistance (Glazed or Unglazed) | 30min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | BMT/CNA/F15084* | Winkhaus UK Ltd | Winkhaus Timber Frame with Halspan Blank (Glazed or Unglazed) | 30min | EN 1634-1 |
| Smoke | N/A | - | | | N/A |
| Fire | BMT/CNA/F15084* | Winkhaus UK Ltd | Winkhaus Timber Frame with Halspan Blank (Unglazed Only) | 60min | EN 1634-1 |
| Smoke | N/A | - | | | N/A |

*Please note that BMT/CNA/F15084 is currently only applicable for use by Factory 2 (Leeds) site.

Test Reports

Test reports cannot be used in conjunction with any primary FoA reports, other test reports or associated documents. They must be followed precisely without any deviation whatsoever.

No specification or parameter changes are allowed at all from that stated within the test report such as size, shape, design, glazing, leaf/frame specification, hardware etc.

| Test Report | Owner of Test Report | Doorset Description | Rating | Test Type |
|-------------|----------------------|---------------------|--------|-----------|
| - | - | - | - | - |